



PRODUCT SPECIFICATION SHEET

SV-15 SV-15 Inkjet Opaque Scrim Vinyl

SV-15 Inkjet Opaque Scrim Vinyl is an ideal choice for indoor banner and signage applications. A high quality reinforced block-out vinyl, SV-15 has multiple laminated layers for durability, opacity and temperature resistance; SV-15 is a premier choice for resolution and color reproductions. SV-15 can be used with grommets for a variety of uses.

Properties
Coating: Polymeric Non-toxic
Surface: White - Matte
Caliper: .0148" (14.8 mil)
Weight: 488 g/m² (14.4 oz/yd²)
Whiteness (CIE Ganz 82): 110
Brightness (TAPPI T452): 94
Gloss (60°): 6.7

Ratings
Health – 0
Reactivity – 0
Flammability – 1 not spontaneously combustible

Environment
Functional temperature range – 50° to 85° Fahrenheit
Functional relative humidity range – 30% to 65%
Ink dry time – varies with type and amount of ink, relative humidity and temperature.

Inks
The inkjet coating of SV15 is designed for use primarily with dye based inks. Although pigmented inks may be used, a slight color gamut difference may be observed.

Applications

Banners	Trade Shows	Displays
Signage	Mapping	Point of Purchase
Posters	Sale Promotions	Artwork

Handling & Storage
Store in cool, dry conditions around 70°F and 20-60% relative humidity
Always place in plastic sleeve when not in use. Never let roll lay flat on its side for extended period as damage could occur, store standing on end or suspended in box with end caps.